

Designed for all users...

## SL2100 Desktop Telephones (TXH-A)

Provides the day to day features required from a desktop telephone.



- > Easy to use
- > No training required using the Curser keys and Feature Keys to access system features
- > Frequent features at the touch of a button using programmable keys
- > Clear display information
- > Home/remote worker
- > Robust and reliable business telephone

### Built-in features

- > Adjustable angle (2 step)
- > Programmable keys with lamps
- > Navigation keys
- > Half duplex speakerphone
- > 100 number personal directory
- > Built in wall mount kit
- > Dual colour call indicator lamp
- > 8 selectable ring tones
- > Energy saving sleep mode

### At a Glance

- > Available with either 12 or 24 programmable buttons
- > Additional 60 button DSS console available
- > Available in black colour
- > 2 line display
- > DESI labels for personalisation of programmable buttons



- 1 IP7WW-12TXH-A1 TEL(BK) - Ordering code: BE116513
- 2 IP7WW-24TXH-A1 TEL(BK) - Ordering code: BE116514
- 3 IP7WW-60D DSS-A1 CONSOLE (BK) - Ordering code: BE116518

Features SL2100 Desktop Telephones (TXH-A)		
LCD Display	Resolution	16 character x 2 line (adjustable contrast)
	Backlit display	No
	Tilttable	No
Keypad	Fixed Feature key	Transfer, DND/Conference, Mute, Flash, Speaker & Hold plus Menu and Curser keys used for Volume, Directory & Call History
	Backlit keypad	No
	Hot keypad (Auto off-hook)	Yes
	Programmable keys	IP7WW-12TXH-A1 = 12 IP7WW-24TXH-A1 = 24
	Softkeys	None
	Curser keys	Yes
	Self-labelling keys	No (DESI label for Programmable keys)
Lamps	Incoming call/Message waiting lamp	2 Colours - Red/Green
	Programmable keys	2 Colours - Red/Green
	Hold	1 Colour – Green
	Speaker/Mute/DND Conf	1 Colour – Red
Physical port	System interface	IP7WW-308-A1 or IP7WW-008-A1 card
	Headset	No
Directory	Personal	100
	System	1000
Sound	Hands-free	Half Duplex
	Handset	Full Duplex, Hearing Aid compatible
	Selectable ring tone	8 Internal/External call selection
	Hold music	System music source
Optional Adapters and consoles	Terminal adapters	None
	DSS console	60 button IP7WW-DSS-A1
Installation	Desk	Adjustable angle – 2 step
	Wall	Yes – Integral mounting within base
Characteristics	Dimensions (wxdxh)	181x221x136/168 mm
	Weight	0.82 kg
	Powering	Line powered
	Colour	Black
Standards	Electrical	EN 55032, EN 55024 Class B
	ROHS	Compliant
	Safety	EN60950-1
Environmental	Operating conditions	Temperature: 0 to +40° C Humidity: 10 to 90% (non-condensing)
	Storage	Ambient Temperature Range: -20 to 60° C, Ambient Humidity: 10 to 90% RH
Compatible Systems	SL1000	Yes – Main Software support required
	SL1100	No
	SL2100	Yes – with System Interface card support
	SV9100	No

For further information please contact NEC EMEA or:

EMEA (Europe, Middle East, Africa)  
NEC Enterprise Solutions  
[www.nec-enterprise.com](http://www.nec-enterprise.com)